

MODEL	Usefull length	Prebending capacity	Bending capacity	Top and Bottom roll dia	Lateral roll dia	Min. bending dia	Motor power	Working speed	Length	Width	Height	Weight
	mm	mm (x1.5/x5)	mm (x1.5/x5)	mm	mm	mm (x1.5/x5)	kw	m/min. (dk.)	mm	mm	mm	kg
3R HMS 2050 x 275	2050	12/15	15/18	275	250	410/1375	11	1,5+5	4350	1520	1700	4750
3R HMS 2050 x 300	2050	15/18	18/22	300	275	450/1500	11	1,5+5	4350	1640	2000	5250
3R HMS 2550 x 275	2550	10/12	12/15	275	250	410/1375	11	1,5+5	4850	1520	1700	5500
3R HMS 2550 x 300	2550	12/15	15/18	300	275	450/1500	11	1,5+5	4850	1640	2000	6250
3R HMS 3100 x 275	3050	8/10	10/12	275	250	410/1375	11	1,5+5	5400	1520	1700	6400
3RHMS 3100 x 300	3050	10/12	12/15	300	275	450/1500	11	1,5+5	5400	1640	2000	7250
3R HMS 4100 x 275	4050	4/6	6/8	275	250	410/1375	11	1,5+5	6400	1520	1700	8200
3R HMS 4100 x 300	4050	6/8	8/10	300	275	450/1500	11	1,5+5	6400	1640	2000	9000